



Esprecious™ One-Touch Fully Automatic Espresso Brewer by Bravilor Bonamat

Consistently crafts exceptional espresso based beverages.

Espresso brewer

- Advanced programming capabilities, combined with a user-friendly experience. Full control over the brewing process including grind, strength and pressure.
- Combines freshly ground beans, powdered milk, chocolate and a precise high-pressure extraction process to create high-quality shots and specialty espresso based beverages.
- Height adjustable, dual pour beverage outlet.
- Separate hot water outlet.
- 8 drink options in up to 3 sizes.

Expand your offerings with ease

The ESPRECIOUS™ is an one-touch automatic espresso brewer serving barista quality specialty beverages with the touch of a button. No highly trained personnel required, and always freshly ground and brewed.

Delight your customers with every sip of every beverage. It's the perfect compliment to sophisticated work cultures and customers.

Get in touch now for pricing & information.

Bravilor Bonamat, LLC | 1204 Biliter Road | Aurora, IL | 60502 | USA
PH 630-423-9400 | FAX 630-423-9405 | E sales.us@bravilor.com | W www.bravilor.com/en-us

**BRAVILOR
BONAMAT**



Create a Stand Alone Coffee Station

Maximize options for coffee service placements. Combine the ESPRECIOUS™ with a cabinet (and the open bottom waste chute shown below) to increase waste disposal space and service locations without counter space.



Accessories

(Left) Extended bean hopper doubles the whole bean capacity.

(Right) Open bottom waste chute fits inside equipment, moving waste under the counter and replaces the interior waste bin.



7.270.610.101



7.231.116.101

One-Touch Fully Automatic Espresso Brewer
by Bravilor Bonamat

Esprecious™

Technical product specs

Brewer Dimensions	26" H x 13.86" W x 22.36" D 660 H x 352 W x 568 D mm
Dimensions with lid open for refilling	37" H x 13.86 W x 22.36" D 940 H x 352 W x 568 D mm
Volts/Amps/Watts	120 V/20 amps/1800 W
Plug Configuration	Dedicated 120V-20 amp. NEMA 5-20 T-slot
Water Connector	3/4" male, filtered water
Water Pressure	14.5 PSI (1 bar) min.
Average Dispense Time	25 sec/shot
Cup Clearance	2.5-5.43"/63.5-138 mm
Cup Sizes	up to 16 oz.
Bean Capacity Esp. 12	1 x 3 lbs./1 x 1.4 KG
Bean Capacity Esp. 22	2 x 1.5 lbs./2 x 1.7 KG
Soluble Capacity	2 x 1.5-2 lbs./2 x 1.3 liters
Tank Volume	0.8 gallons/3.02 liters
Weight	<u>NET</u> : 68 lbs./30.84 KG <u>SHIP</u> : 78 lbs./35.38 KG
Certifications	NSF/ANSI 372, C-UL (CA & USA)

Model numbers

8.035.192.41001

7.270.609.101

8.035.202.41001

7.270.610.101

7.980.000.136

7.290.107.101

7.231.116.101

7.270.616.101

7.270.801.101

7.270.803.101

7.270.617.101

7.193.101.102

6.980.000.677

6.980.000.752

6.980.000.753

ESPRECIOUS™ 12

Bean Canister extension - ESP. 12

ESPRECIOUS™ 22

Bean Canister extension - ESP. 22
33" High Cabinet for ESPRECIOUS

Waste Chute

Waste bin for under-counter waste disposal

MDB Interface for payment systems

Housing for coin changer

Front panel for housing (use in combination with customers system)

Drip tray with drainage kit

Espresso cleaning tablets (12 jars)

Essential spare parts kit

Sanitation kit

Preventive Maintenance kit